

# Specifications



Photo is representative



## Eaton 5E700I

Eaton 5E Gen2 UPS IEC, 700 VA, 360 W,  
Input: C14, Outputs: (4) C13, Tower

### General Specifications

PRODUCT NAME	Eaton 5E Gen2 UPS
CATALOG NUMBER	5E700I
EAN	3553340704130
PRODUCT LENGTH/DEPTH	288 mm
PRODUCT HEIGHT	148 mm
PRODUCT WIDTH	100 mm
PRODUCT WEIGHT	4.14 kg
COMPLIANCES	CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC UKCA Cm Ukr IEC/EN 62040-3



Powering Business Worldwide

## Product specifications

### SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design

TOPOLOGY	Line-interactive
FORM FACTOR	Tower
CONSTRUCTION TYPE	Free standing model
COLOR	Black
VA RATING	700 VA
WATTAGE	360 W
RACK MOUNTING KIT	No

### PACKAGE CONTENTS

- (2) IEC-IEC output cables
- Quick start
- Safety instructions

SURGE PROTECTION	Yes
INTERNAL BYPASS	No
HOT SWAP POWER	No
AUTO SHUTDOWN FUNCTION	No
PRIMARY FREQUENCY - MAX	63 Hz
PRIMARY FREQUENCY - MIN	45 Hz
INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	45-63 Hz
RECEPTACLE	(4) C13
NUMBER OF OUTPUTS C13	4
VOLTAGE	230V
OUTPUT NOMINAL VOLTAGE	230V
FEED TYPE	1
VOLTAGE TYPE	AC
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	Automatic battery test,

## Resources

### BROCHURES

[eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf](#)

### CERTIFICATION REPORTS

[eaton-dpq-5egen2-ups-certificate-en-gb.pdf](#)

### MANUALS AND USER GUIDES

[eaton-dpq-5egen2-ups-manual-en-gb.pdf](#)

### TECHNICAL DATA SHEETS

[eaton-dpq-5egen2-ups-datasheet-en-gb.pdf](#)

	deep-discharge protection, cold-start capable
<b>BATTERY RATING</b>	12 V / 7 Ah
<b>BATTERY TYPE</b>	Sealed, lead-acid
<b>EXTENDED BATTERY CAPABILITY</b>	No
<b>EXPANSION SLOTS</b>	No
<b>ETHERNET INTERFACE</b>	No
<b>INCLUDES NETWORK CARD</b>	No
<b>USER INTERFACE</b>	LEDs
<b>TYPE OF INTERFACE</b>	None
<b>POTENTIAL FREE SWITCH CONTACT</b>	No
<b>RELATIVE HUMIDITY</b>	0-90% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F)
<b>OPERATING TEMPERATURE - MAX</b>	40 °C
<b>OPERATING TEMPERATURE - MIN</b>	0 °C
<b>OUTPUT APPARENT POWER</b>	700 VA
<b>INPUT VOLTAGE - MAX</b>	300 V
<b>INPUT VOLTAGE - MIN</b>	140 V
<b>OUTPUT VOLTAGE - MAX</b>	257 V
<b>OUTPUT VOLTAGE - MIN</b>	195 V
<b>SECONDARY FREQUENCY - MAX</b>	60 Hz
<b>SECONDARY FREQUENCY - MIN</b>	50 Hz
<b>BATTERY QUANTITY</b>	1
<b>EFFICIENCY AT MAX. LOAD</b>	95
<b>INPUT VOLTAGE RANGE</b>	140-300 V
<b>OUTPUT FREQUENCY</b>	50/60 Hz
<b>OUTPUT VOLTAGE RANGE</b>	195-257 V
<b>PHASE (INPUT)</b>	1
<b>PHASE (OUTPUT)</b>	1
<b>POWER CONSUMPTION</b>	18.9 W

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

