

Specifikācijas



Foto ir ilustratīvs



Eaton 5E900UI

Eaton 5E Gen2 UPS USB IEC, 900 VA, 480 W,
Input: C14, Outputs: (4) C13, Tower

Vispārējā informācija

PRODUCT NAME	Eaton 5E Gen2 UPS
--------------	-------------------

CATALOG NUMBER	5E900UI
----------------	---------

EAN	3553340704222
-----	---------------

PRODUCT LENGTH/DEPTH	288 mm
----------------------	--------

PRODUCT HEIGHT	148 mm
----------------	--------

PRODUCT WIDTH	100 mm
---------------	--------

PRODUCT WEIGHT	5.1 kg
----------------	--------

COMPLIANCES	CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive
-------------	--

CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC UKCA Cm Ukr IEC/EN 62040-3
----------------	--

Battery	
BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY QUANTITY	1
BATTERY MANAGEMENT	Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 9 Ah
EXTENDED BATTERY CAPABILITY	No

Electrical input	
INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50/60 Hz
INPUT VOLTAGE RANGE	140-300 V
INPUT FREQUENCY RANGE	45-63 Hz

Environmental	
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	0-90% non-condensing

Electrical output	
RECEPTACLE	(4) C13
VOLTAGE	230V
WATTAGE	480 W
OUTPUT VOLTAGE RANGE	195-257 V
OUTPUT NOMINAL VOLTAGE	230V
FEED TYPE	1
TOPOLOGY	Line-interactive
VA RATING	700 VA

Communications	
INCLUDES NETWORK CARD	No
COMMUNICATION	USB port (HID compliant)
ETHERNET INTERFACE	No
USER INTERFACE	LEDs
POTENTIAL FREE SWITCH CONTACT	No
EXPANSION SLOTS	No
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
TYPE OF INTERFACE	USB

Additional specifications	
CONSTRUCTION TYPE	Free standing model
PACKAGE CONTENTS	• (2) IEC-IEC output cables • Quick start • Safety instructions
PHASE (OUTPUT)	1
INTERNAL BYPASS	No
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
EFFICIENCY AT MAX. LOAD	95

RACK MOUNTING KIT	No
PHASE (INPUT)	1
SURGE PROTECTION	Yes
HOT SWAP POWER	No

Informatīvie materiāli

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATUMS:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Īrija
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Visas tiesības paturētas